

Seat Belts for Forklift

Forklift Seat Belts - Described in the Regulation guidelines are the utilization of seatbelts and operator restraints on forklifts. It states that the responsibility falls on the employers' to be able to make certain that each machine, piece of equipment and tool is used properly utilized according to the directions of the maker.

Rough Terrain lift trucks need to meet the regulations of ANSI Standard ASME B56.6-1992 regarding their design, maintenance, inspection, fabrication and use.

Side boom tractors and mobile equipment along with a Rollover Protective Structure, or ROPS for short, need to have seat belts which meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile machine includes seat belts required by law, the driver and subsequent passengers ought to ensure they use the belts each time the motor vehicle is in motion or engaged in operation because this could cause the machinery to become unsteady and hence, not safe.

If a seat belt or various operator restraint is needed on a lift truck.

The seat belt requirements while working a forklift depend on different factors. Whether the lift truck is equipped with a Rollover Protective Structure, the kind of forklift itself and the year the forklift was actually manufactured all add to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, system or enclosure, ANSI Standard ASME B56.1-1993 with regards to powered industrial trucks, is intended to assist the operator in lessening the danger of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device may include a seat belt, though a seat belt is not necessarily a part of such equipment or system.